

ANCILLARIES

# MT167 – MACROFAN UHS SPEEDY ACCELERATOR



Ready for use

## DESCRIPTION

Accelerator for 2K UHS refinish field.

### USE

Suitable to speed up the drying process of 2K UHS finishes when faster drying at low temperatures is required or the painting process has to be accelerated (e.g. touch-ups or partial painting at lower temperatures than 30°C).

### **CHARACTERISTICS**

- Drying speed increase
- Earlier polishing time
- Unaltered aesthetical aspect of the finish

### APPLICATION

Add up to **5%** according to type of product (for the right percentage we recommend you to consult the technical data sheet for each product).

The additive addition replaces the thinner.

### NOTES

The addition of MT167 considerably modifies the products' pot life: it is, therefore, recommended to apply the product just after this addition.

Higher additions than indicated can damage the final aesthetical aspect and the films resistance over time: we recommend, therefore, to take great care in the addition of this product and to never exceed the recommended quantities indicated in the relevant technical data sheets.

#### TECHNICAL DATA SHEET N° 0651-GB UPDATED 01/2010

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.