




## EL010 – ENERGY LINE PLASTIC PRIMER



Ready for use



Air drying at 20° C:  
20-30 min.

### DESCRIPTION

Universal one-pack primer suitable for plastics, ready for use in an aerosol.

### USE

In Car Refinish as an adhesive primer for all plastics used in the car field.  
Special product for small parts and small touch-ups in the refinish field.

### CHARACTERISTICS

- Easy to use - ready for use (aerosol)
- Excellent adhesion directly to plastics
- Quick drying
- Safe use
- Slightly silver coloured for an easier application

### SUBSTRATE PREPARATION

Degrease carefully with 00665 HYDROCLEANER SLOW / 00699 HYDROCLEANER.  
For further information about the product use in FAST REPAIRS cycles see the Painting Process TDS N° 007.

### APPLICATION

Spraying.  
**Ready for use.** Shake well 2-3 minutes before use.

Spray temperature: 15-30° C  
N° of coats: 1 cross coat  
Spray distance: 20-25 cm  
Recommended film thickness: 5-10 µ  
**DIR 2004/42/CE: Special finishes IIB/e – VOC ready for use 840 g/l**  
**This product ready for use contains at most <840 g/l VOC**

### DRYING TIMES

**Air drying at 20°C**  
20-30 min.

---

## **OVERCOATING**

Fillers and top coats from the Lechler range can be over applied without sanding after flash-off.  
For further information about the product use in FAST REPAIRS cycles see the Painting Process TDS N° 007.

---

## **NOTE**

ATTENTION: the product is not suitable for the painting of polyethylene substrates (PE). Polyethylene is used for some tanks and motorcycles' details.

After use turn the aerosol upside down and spray the rest out of the supplying pipe in order to avoid blockage problems during the storage time before the following use.

SHELF LIFE AT 20°C: 24 months

**TECHNICAL DATA SHEET N° 0498-GB**  
**UPDATED 04/2013**

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.